



PMC Type 8202  
Pushbutton Telegraph  
**QUESTIONNAIRE**

QUOTE No \_\_\_\_\_

---

**PROJECT DETAILS**

**Shipyard**

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Address: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tel: \_\_\_\_\_

Fax: \_\_\_\_\_

email: \_\_\_\_\_

**Purchaser / Agent**

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Address: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tel: \_\_\_\_\_

Fax: \_\_\_\_\_

email: \_\_\_\_\_

**Owner**

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Address: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tel: \_\_\_\_\_

Fax: \_\_\_\_\_

email: \_\_\_\_\_

Ref. #: \_\_\_\_\_

PO #: \_\_\_\_\_

Ship Date: \_\_\_\_\_

Ship To: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**VESSEL DETAILS**

Vessel Type: \_\_\_\_\_

Hull Type: \_\_\_\_\_

Length: \_\_\_\_\_

Beam: \_\_\_\_\_

Draft: \_\_\_\_\_

Deadrise: \_\_\_\_\_

Displacement: \_\_\_\_\_

Est. Top Speed: \_\_\_\_\_

Est. Cruise Speed: \_\_\_\_\_

Est. Min Speed: \_\_\_\_\_

Vessel Name: \_\_\_\_\_

Model Name: \_\_\_\_\_

Year Built: \_\_\_\_\_

Hull Number: \_\_\_\_\_

IMO Number: \_\_\_\_\_

Regulatory Body: \_\_\_\_\_

Class: \_\_\_\_\_

Class Notations: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



PMC Type 8202  
Pushbutton Telegraph  
**QUESTIONNAIRE**

QUOTE No \_\_\_\_\_

- Number of shafts:
- Single screw
  - Twin screw
  - Double ended, twin screw
  - Other (specify) \_\_\_\_\_

- Number of Telegraph Stations:
- Bridge \_\_\_\_\_
  - Engine Control Room \_\_\_\_\_
  - Local At Engine \_\_\_\_\_

- Outside Stations:  Specify QTY and location \_\_\_\_\_

- Machinery Wrong Direction Alarm:
- Not Required
  - Required

- Audible Devices:
- Not required
  - Number of Telegraph Order Bells per station \_\_\_\_\_
  - Number of Wrong Direction Bells per station \_\_\_\_\_

**Note:** This is an owner preference. A single bell per station can be wired to twin screw telegraph order alarms in addition to twin screw wrong direction alarms.

- Data Logger Output Signals  NMEA 0183

- Power Sources Available:
- 24 VDC (prefered)
  - 120 VAC 60 Hz
  - Other (specify) \_\_\_\_\_

**Note:** Classification Society may require battery back up (UPS)